



NOTES:

1. A PERMIT WILL BE REQUIRED FOR ANY CONNECTION INTO A CITY UTILITY. A SCALED DRAWING IS REQUIRED.
2. DRAIN LINE IS PRIVATE AND OWNER IS RESPONSIBLE FOR ALL MAINTENANCE AND REPAIR TO LINE.
3. RESTORATION OF THE PARKWAY (WHEN APPLICABLE) WILL REQUIRE USING 4" OF TOP SOIL, SOD AND WATERING TO ENSURE GROWTH.
4. CONNECTION TO STORM SEWER PIPE SHALL BE CORED AND BOOTED OR HYDRAULIC CEMENTED. CONNECTION MUST BE INSPECTED PRIOR TO BEING BACKFILLED.
5. "JULIE" LOCATES ARE REQUIRED PRIOR TO ANY EXCAVATIONS.
6. WHEN CONNECTING TO A PVC STORM SEWER, THE USE OF A SADDLE IS MANDATORY.
7. ALL EXCAVATIONS MUST BE BARRICADED SECURELY.
8. USE CITY STANDARD UG-03 FOR TRENCH CROSS SECTION WHEN INSTALLING UNDER OR WITHIN 2' OF A PAVED SURFACE.

| |
|--|
| Revised: |
| 1. 06/12/2015 |
| 2. KL 1/25/2021 INCLUDE DOWNSPOUT CONNECTIONS |
| 3. JRG 8/18/2023 NOTE 9 REMOVED (\$10,000 LICENSE) |
| 4. |

| |
|--|
| Drawing Name |
| SUMP PUMP OR DOWNSPOUT CONNECTION |

| |
|--------------------|
| Drawing Number |
| UD-04 |
| Date: 05/28/2015 |
| Drawn Checked |
| JH AW |

